

Product Data Sheet

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

GUIDEMAX SERIES

Guide Max Series are premium quality slideways lubricants specifically design to meet the requeriments for accuracy, aqueous coolant separability and equipment protection of precision machine tools.

Guide Oil Max are formulated from synthetic blend base stocks and performance balanced with an advanced additive system that provide controlled frictional properties, compatibility with aqueous metalworking fluids and corrosion protection of parts and equipment.

Guide Max Series provides the following benefits:

- Helps eliminate stick slip; allows consistently accurate machining.
- Suitable for a wide range of way material combinations allowing for product consolidation.
- Prevents removal of lubricants from critical surfaces.
- Help to reduce the deterioration of sliding surface.

Physical Properties

PRODUCTS	GUIDE-32	GUIDE-68	GUIDE-220
ISO Grade	32	68	220
Viscosity			
@ 40°C, cSt	32.68	68	220
@ 100°C, cSt	5.38	8.57	18.82
Viscosity Index	97	96	96
Specific Gravity	0.8767	0.8863	0.8848
Flash Point, °F (°C)	428 (220)	428 (220)	464 (240)
Apparence	Yellow	Yellow	Yellow

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.