

Product Sheet

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

AIR PRESSMAX SERIES

Air Compressor

Brautek Pressmax Series is formulated with synthetic oil and highly destiled petroleum base oil, reinforced with powerful additives. It is designed for lubricating rotative and reciprocating air compressors and vacuum pumps. The lighter grades are also recommended for gas and steam turbine applications.

Air Pressmax Series are manufactured using the highest quality base stocks, additive treated with rust and corrosion inhibitors, oxidation control agents, anti-wear compounds and defoamants and is exceptional at controlling sludge and deposits.

Physical Properties

PRODUCTS	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150
ISO Grade	32	46	68	100	150
Viscosity @ 40°C, cSt	32.2	46.0	68.0	100.0	149.0
@ 100°C, cSt	5.6	7.1	9.25	11.78	15.44
Viscosity Index	113	112	112	106	105
Specific Gravity	0.877	0.876	0.876	0.876	0.879
Pour Point, °F (°C)	-44 (-42)	-38 (-38)	-38 (-38)	-33 (-36)	-27 (-33)
Flash Point, °F (°C)	440 (227)	470 (243)	470 (243)	520 (271)	495 (257)
Four Ball Wear, mm	0.6	0.6	0.6	0.6	0.6

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.