

SYNAULIK SHO SERIES

Synaulik SHO Series hydraulic oils are formulated from the highest quality synthetic hydrocarbons (PAO) to meet the requirements of all types of hydraulic systems. Synaulik SHO Series are rust and oxidation inhibited to protect against rust, wear and the formation of sludge. They are compatible with seal materials normally used in hydraulic systems.

Synaulik SHO Series hydraulic oils contain additives necessary to meet requirements for Denison HF-O, Vickers industrial and mobile applications and Cincinnati Milacron P-68, P-69 and P-70 specifications.

Physical Properties

PRODUCTS	22	32	46	68
ISO Grade	22	32	46	68
Viscosity @ 40°C, cSt	22.0	32.0	46	68
@ 100°C, cSt	4.7	6.1	8	10.7
Viscosity Index	136	142	146	146
Flash Point, °F (°C)	451 (233)	465 (243)	470 (268)	480 (271)
Fire Point, °F (°C)	491 (255)	495 (257)	505 (263)	564 (268)
Pour Point, °F (°C)	-60 (-54)	-60 (-54)	-55 (-41)	-40 (-42)

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.